(19)日本国特許庁 (Jド) (12)

(12)公表特許公報(A)

(11)物育出願公表番号

特表平10-510158

(43)公表日 平成10年(1995)10月6日

(61) Int.C1*	議列記号	Fi	
C 1 2M 1/00		C12M 1/00	Z
BO3C 1/28		B 8 8 C 1/28	
C12N 15/09		C12Q 1/69	A
C12Q 1/68		C 1 2 N 15/00	A
		卷查萧求 未萧求	子楊齊政府求 有 (全 45 更)
(21)出願證号	妹 年 字8~517831	(Tt)出版人 ガメラ・パイオサイエンス・コーポレイシ	
(86) (22) 出職日	22) 出版日 平成7年(19%) 12月8日 ヨン		
(85)翻訳文提出日	R文指出日 平成9年(1997)6月9日 アメリカ会像国(21957サテュー		今候国(21号)でサチューセッツ州
(86) 劉際出職語号	PCT/US95/16256	ア/US95/16256 メットフォード、ポストン・アベニュー	
(87)国際公演番号	WO95/17959	20048	
(87) 國際公議日	平成8年(1996)6月13日	(72)発明者 マイアン、アレック	
(31)優先核主張錯号	08/353.573	53.573 アメリカ合衆国の139マサチューセッツ州	
(32) 優先日	1994年12月9日	オンプ	リッジ、マガジン・ストリート
(33) 新発権主義協	未提 (US)	[37番	
		(74)代權人 奔瓊士 计	宇山 藻 (外2名)


(54) 【発明の名称】 磁気サイクル反応を行うための接触

(67) [3589]

本短期は、超越電による前離線の分解に番づいて、鈴彦 の機能服用の増端方法を行うための貨幣を提供する。こ の分離手数は、増雄方法における中程ポリスラーゼの使 用を可能とし、それによって、その時報方法の延度およ び正確さ、さらにはまた、増継することができる幅的候 機の大きなを映大させる。

Figure 2A

最終實に続く



* NOTICES *

JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

- 1. It is a device for performing a magnetic cycle reaction, (a) A temperature control means of a temperature control sample block (some magnetic cycle reaction sample tubes are attached in sample tube WERU) containing a plate containing sample tube WERU of a large number located in a line in a row, and a sample block:
- (b) The 1st magnetism element and its 1st magnetism element are located a sample block top and near it. A flow of current which passes along a wire which the 1st magnetism element contains a coil of a large number located in a line in a row, and the coil contains an electrical conduction wire of many volumes in the surroundings of an elasticity iron core, and contains the coil produces a magnetic field around the 1st magnetism element.;
- (c) The 2nd magnetism element and its 2nd magnetism element are located the bottom of a sample block, and near it, A flow of current which passes along a wire which the 2nd magnetism element contains a coil of a large number located in a line in a row, and the coil contains an electrical conduction wire of many volumes in the surroundings of an elasticity iron core, and contains the coil produces a magnetic field around the 2nd magnetism element.;
- A control device containing a microprocessor and its control device (d) A temperature control sample block, And it is connected effective in each of the 1st magnetism element and the 2nd magnetism element. The control device is connected effective also in a user interface again, A device included combining a power supply which the control device is connected effective in; and the (e) control device which control a flow of current which passes along each magnetic element, and temperature of a temperature control sample block, and supplies electric power to a device.
- and temperature or a temperature control sample block, and supplies electric power to a device.

 2. Use the device according to claim 1, it is how to perform a magnetic cycle reaction for amplifying a specific DNA fragment, include (a) solid phase primer in a nucleic acid chain complementary to target nucleic acid, and make a solid phase chain combined with target nucleic acid.
- (b) Separate a solid phase chain and target nucleic acid.:
- (c) Include a magnetic primer in a nucleic acid chain complementary to a solid phase chain, and obtain a double chain which has one solid phase chain and one magnetic chain.;
- (d) Separate a solid phase chain from a magnetic chain by applying an electromagnetic field of sufficient intensity to dissociate a double chain by generating a magnetic field in the 1st magnetism element of the device according to claim 1;
- (e) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain by applying an electromagnetic field by generating a magnetic field in the 2nd magnetism element of the device according to claim 1;
- (f) A way only the number of times required to elongate an annealed primer by suitable DNA polymerase, and obtain amplification DNA of quantity of, and the (g) request includes repeating a process of (d) (f).

- 3. Use the device according to claim 1, it is a method for amplifying specific single strand target nucleic acid, include (a) magnetism primer in a nucleic acid chain complementary to target nucleic acid, and make a magnetic chain combined with target nucleic acid.;
- (b) Separate a magnetic chain and target nucleic acid.;
- (c) Include a solid phase primer in a nucleic acid chain complementary to a magnetic chain, and obtain a double chain which has one solid phase chain and one magnetic chain.;
- (d) Separate a solid phase chain from a magnetic chain by applying an electromagnetic field of sufficient intensity to dissociate a double chain by generating a magnetic field in the 1st magnetism element of the device according to claim 1;
- (e) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain by generating a magnetic field in the 2nd magnetism element of the device according to claim 1.;
- (f) A way only the number of times required to elongate an annealed primer by suitable DNA polymerase, and obtain amplification DNA of quantity of; and the (g) request includes a process of repeating a process of (d) – (f).
- 4. Use the device according to claim 1, it is a method for amplifying specific double strand target nucleic acid, separate a chain of (a) target nucleic acid, and obtain the 1st chain and 2nd chain.;
- (b) Include a solid phase primer in a chain complementary to the 1st chain, obtain the 1st heteroduplex that has the 1st chain and solid phase chain, and include a magnetic primer in a chain complementary to the 2nd chain, and obtain the 2nd heteroduplex that has the 2nd chain and magnetic chain.;
- (c) Separate the 1st heteroduplex and 2nd heteroduplex.;
- (d) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain.;
- (f) elongating an annealed primer by suitable DNA polymerase —; and (g) separating a solid phase chain from a magnetic chain by applying an electromagnetic field of sufficient intensity to dissociate a double chain by generating a magnetic field in the 1st magnetism element of the device according to claim 1 —;
- (h) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain by generating a magnetic field in the 2nd magnetism element of the device according to claim 1.;

 A way only the number of times required to elongate an annealed primer by suitable DNA polymerase, and obtain amplification DNA of quantity of; and the (j) request includes a process of

[Translation done.]

repeating a process of (g) - (i).